



PANOLIN
Bläsimühle 2 – 6
CH-8322 Madetswil
Switzerland
www.panolin.com



Part of the PANOLIN concepts



PANOLIN SPRINT

Hydraulic fluid – readily biodegradable, synthetic esters

Environmentally Considerate Lubricant (ECL)/Environmentally Acceptable Lubricant (EAL)

Features and benefits

- Fully synthetic, environmentally friendly and readily biodegradable hydraulic fluid
- Based on proven PANOLIN technology
- Ester blend with modified, saturated and unsaturated esters
- Minimally toxic (according to OECD 201/202/203)
- CO₂ reduction due to extended oil-change and service intervals
- Outstanding anti-wear and anti-corrosion properties
- Prevents deposits in the hydraulic system
- Excellent cold flow characteristics
- Outstanding extreme-pressure characteristics
- Do not mix with other readily biodegradable hydraulic fluids – please refer to our «PANOLIN Conversion and Operating Guidelines» regarding mineral oils, synthetic fluids and PANOLIN ECLs/EALs

Applications (follow manufacturer's instructions)

- In earthmoving and forestry hydraulic systems
- Various machines for industrial manufacturing
- For construction and hydroelectric engineering
- Marine hydraulic systems, e.g. CPP, stabilisers, steering and deck equipment

Environmental compatibility

It is decomposed by micro-organisms in water and/or soil almost without any residues.

- Biodegradability acc. to OECD 301 B: > 60%
- EN 16807
- EU Ecolabel DE/027/289
- Japan Eco Label
- US EPA VIDA (Vessel Incidental Discharge Act), VGP 2013 (Vessel General Permit)
- Water hazard classifications acc. to AwSV: WGK 1

Specifications

ASTM D8029
FZG A/8.3/90: 11
ISO 15380/HEES
Vickers V104 C

Approval (valid manufacturer approval for the specific lubricant)

Coup'eco (34546)



Technical data (mean values, subject to normal tolerances)

PANOLIN SPRINT	Product No.	Density g/cm ³ 15 °C	Viscosity in mm ² /s		Flashpoint COC in °C	Pour point in °C	Viscosity index
			40 °C	100 °C			
32	34544	0.919	34.6	7.4	253	- 42	188
46	34546	0.920	45.9	9.1	274	- 36	185
68	34548	0.929	67.0	11.8	273	- 36	174

Instructions

Please refer to the drum label, or for detailed information, to the safety data sheet – available from PANOLIN.
Before changing over to PANOLIN ECLs/EALs, please ask for our instructions.